



# EpiTech<sup>®</sup>

surface protection films



# Features and Benefits of EpiTech®

Feature	Advantage	Benefit
Tough self adhesive films protect valuable products	Products are safe from damage during manufacture, storage, distribution and fabrication	Saves cost and time in rework or repairs, and ensures the products will remain in the same quality condition as it left the factory
Installations and fabrications can occur whilst surface protection films remain on the product	Components can be installed in an optimal order inspiring confidence that surfaces will remain undamaged without scratches, splotches and contamination	Saves delays during construction and any unnecessary clean up or replacement after construction has been completed
Designed and tested for local conditions	EpiTech® is designed to cope with the demanding UV environments across Australia and New Zealand	Reduced problems from tearing, adhesion, residue and film breakdown
Custom made to specific requirements, which can be single layer or coextruded	Custom films are designed to suit differing products, application methods and use	Custom built to suit specific applications or stock options available
Choices of clear, tinted, coloured and printed films	Clear films for product display, coloured films for direct marking of measurement instructions, and custom printed films	Clear films on glass allow light into work areas during construction, whilst printing offers effective branding



## Product Categories

Carpet, Glass, Wood, Laminates, Flooring, Marble, Stone, Steel, Painted steel, Stainless steel, Aluminium.

## Surface Protection Film

EpiTech® saves you time and money by protecting surfaces during:

- Production
- Forming
- Transport
- Installation

The films are specifically formulated for:

- Application equipment
- Product type
- End usage

EpiTech® protects the working environment:

- Covering carpet during maintenance
- Protecting cabinets/panelling during installation
- Keeping windows clean whilst plastering and painting

EpiTech® is a cost effective way to ensure:

- Your product is delivered and installed in showroom condition
- No fuss during adhesion and removal

## Materials and Printing

The material choices are governed by:

- Type of application machinery
- Film gauge
- Adhesion requirements
- Type of product to be covered
- Durability requirements
- Environment of use (internal/external)

- Films normally consists of LDPE, single layer or co-extruded, with pressure sensitive adhesive on one side
- Film widths can be varied to suit the application up to a maximum of 1470mm
- Printing options of up to 8 colours are available

Contact Aperio:

web: [www.epitech.co.nz](http://www.epitech.co.nz)

web: [www.aperiogroup.com.au](http://www.aperiogroup.com.au)

email: [info@aperiogroup.com.au](mailto:info@aperiogroup.com.au)